

TECHNICAL DATA SHEET

Order No. **456-10101**

Item/Model **Minibar with glass door
model MB 30 UG**

GTIN **4017337071739**



- **Material:** (Housing) powder-coated steel, black; (Interior) plastic, white; (Shelf) plastic, light blue
- Triple-glazed door, double-coated, lockable
- Reversible door hinge
- 1 height-adjustable shelf, W 323 x D 145 mm
- LED interior lighting
- Digital temperature control
- Absorption cooling; extremely quiet (Class A)
- Automatic defrosting
- Temperature range: +5 / +14 °C
- Connection: 230 V - 50 Hz - 0.050 kW
- Capacity (gross/net): 28 / 26 liters
- Interior dimensions: W 312 x D 225 x H 395 mm
- Exterior dimensions: W 402 x D 428 x H 500 mm
- Weight (net/gross): 16 / 22 kg
- Refrigerant: Ammonia (R717)
- Energy efficiency class: G (Scale A to G)

Origin China

customs tariff no. 84181080

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **456-10101**

Item/Model **Minibar with glass door
model MB 30 UG**

GTIN **4017337071739**



Safety and Warning Instructions

- The absorption refrigerator must be placed on a stable, level, and heat-resistant surface.
- The device is designed for dry use and must not come into contact with water. Do not fill the device base with water.
- Operation is only allowed in well-ventilated rooms. Maintain a minimum distance of 12 cm from the back wall and 5 cm from other sides to ensure adequate airflow.
- The refrigerator contains the refrigerant ammonia (R717), which is toxic and hazardous when inhaled, in contact with skin, or harmful to the environment. Avoid direct contact. In case of a leak, ventilate the room immediately, leave the area, and contact qualified personnel.
- Cyclopentane, used as a propellant, is flammable. Avoid contact with open flames or ignition sources.
- In case of visible damage to the device or the refrigerant circuit, immediately stop operation and contact professional personnel.
- Children and unauthorized persons must not operate the device or play near it.
- Protect the device from moisture, direct sunlight, and extreme environmental temperatures.
- The device must only be operated with a grounded power connection. Do not use extension cords or adapters.
- Repairs and maintenance should only be carried out by qualified personnel. Use only original spare parts.
- Before cleaning or extended periods of non-use, unplug the device and ensure it has cooled down.
- Clean the device regularly with a damp cloth and mild detergent. Do not use abrasive cleaners, metal sponges, or chlorine-based cleaning agents.
- In the event of a power failure, keep the door closed as much as possible to maintain the internal temperature.
- The maximum load per shelf is 8 kg, and the door compartments should be loaded with a maximum of 5 kg each.
- Dispose of packaging materials safely and keep them out of reach of children to avoid suffocation hazards.
- At the end of its lifespan, dispose of the device properly at an electronic waste collection point to protect the environment.

Origin China

customs tariff no. 84181080

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry

ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827